

**REMARKS**

In response to the Examiner's requirement, both a marked-up copy and a clean copy of the Substitute Specification are attached hereto. No new matter has been added.


In response to the Examiner's requirement, Applicants respectfully decline to file a new oath or declaration. The Declaration filed February 27, 2006 is sufficient to comply with U.S. patent practice as the only amendments made to the specification herein are the insertion of headings and a reference to priority information. No substantive amendments have been made to the substitute specification or the claims.

In view of the above, each of the presently pending claims in this application is believed to be in immediate condition for allowance. Accordingly, the Examiner is respectfully requested to withdraw the outstanding rejection of the claims and to pass this application to issue. If it is determined that a telephone conference would expedite the prosecution of this application, the Examiner is invited to telephone the undersigned at the number given below.

In the event the U.S. Patent and Trademark office determines that an extension and/or other relief is required, applicant petitions for any required relief including extensions of time and authorizes the Commissioner to charge the cost of such petitions and/or other fees due in connection with the filing of this document to Deposit Account No. 03-1952 referencing docket no. 449122078900.

Dated: December 22, 2006

Respectfully submitted,

By  # 54,217 f.o.

Kevin R. Spivak

Registration No.: 43,148  
MORRISON & FOERSTER LLP  
1650 Tysons Blvd, Suite 300  
McLean, Virginia 22102  
(703) 760-7762

**AVOIDANCE OF TRANSCODING OR INTERRUPTION IN THE EVENT OF  
PAYLOAD CODING EXCHANGES IN EXISTING CONNECTIONS**



CLAIM FOR PRIORITY

This application is a national stage of PCT/DE2003/002223,  
published in the German language on January 15, 2004, and which  
claims the benefit of priority to German Application No. DE 102  
31 027.0, filed on July 9, 2002.

TECHNICAL FIELD OF THE INVENTION

10 The invention relates to a method and devices for signaling a  
modification of the coding of a user data connection section  
termination at a media gateway from a media gateway controller  
to the media gateway.

15 BACKGROUND OF THE INVENTION

In ITU-T protocols H.248 and Q.1950 the control of so-called  
media gateways (MGWs = switching devices in particular in a  
cellular mobile radio network or fixed network) is specified by  
so-called media gateway controllers (MGCs). The protocol Q.1950  
20 is used in conjunction with the BICC protocol Q.1902.4 also  
specified by the ITU-T. These protocols can also be used for  
3GPP applications. Media gateways for example connect user  
connection sections (for the transmission of user data such as  
voice, text, multimedia) of a telecommunication network and in  
25 some instances convert different codings, e.g. voice codings  
such as G.711 or AMR, to each other. User connection section  
termination, abbreviated to termination, refers below to the  
termination of a section of a user connection switched through  
the MGW, e.g. for voice or multimedia (sound and image) at this  
30 MGW. The MGW sends and/or receives (user) data associated with  
the user connection through said termination. In the parlance

of the protocols H.248 and Q.1950 a so-called termination corresponds to a user connection section termination.

The above-mentioned protocols allow existing user connections  
5 to be modified, e.g. by selecting a different coding. The  
signaling thereby used between MGC and MGW (protocols H.248 and  
Q.1950) is such that each termination into the MGW is modified  
irrespective of the other terminations connected to it within  
the MGW. For example the MGW can be instructed to use a  
10 different coding at this termination or to send and/or receive  
no data. When a termination is modified, the MGW does not know  
whether other connections also connected by it to said  
termination will also be modified later. Therefore when a  
termination is modified the MGW must immediately implement  
15 measures if different codings result in connected terminations  
(in the parlance of the protocols H.248 and Q.1950  
interconnected terminations are located within an MGW in a so-  
called common context) and these are converted to each other  
for example by so-called transcoding. In specific cases however  
20 the coding of all terminations interconnected into the MGW,  
which are in the same context, should be modified almost  
simultaneously, for example in the context of the so-called  
BICC codec modification or codec renegotiation (see Q.1902.4),  
by means of which the coding of existing voice connections can  
25 be modified. The 3GPP also uses the said BICC procedures to  
switch existing user connections between voice and multimedia  
(i.e. a combination of voice and image in a common coding). The  
MGC can identify such situations based on the so-called call  
control signaling coming into it, e.g. Q.1902.4. As the  
30 signaling of the MGC to the MGW is sequential, in the event of  
almost simultaneous switching of all connected terminations  
within an MGW a possibly unwanted response results. The MGW  
briefly activates a transcoder, which is then almost  
immediately deactivated again. This generates an unnecessary

workload in an MGW and reduces its throughput. It would be acceptable but has hitherto not been technically possible to break the connection for a short time. When the first termination is modified, the MGW may also determine that it cannot convert the new coding of this termination into the coding still used at the other termination(s). This can happen for example when switching between a voice connection and a multimedia connection or a general data connection. In this case the MGW therefore rejects the modification of the user connection via H.248/Q.1950 signaling.

#### SUMMARY OF THE INVENTION

The ~~object of the present invention is to~~ enables the most efficient possible switching of codings in terminations at a media gateway on the instruction of a media gateway controller and to enable switching between codings, which the media gateway cannot convert to each other. The object is achieved respectively by the subject matter of the independent Claims. According to the invention an unnecessary workload due to the brief powering up and powering down of a transcoder into the MGW can be avoided in that the media gateway controller instructs the media gateway by appropriate signaling only to implement a verification of the connectability of terminations after receipt of a plurality of instructions to modify the coding of a termination (and in some instances receipt of a specific instruction to start a comparison) (because the powering up of a transcoder would only take place after a comparison showing that the terminations to be connected or which have already been connected during a coding modification no longer use the same coding, which is not the case here). Switching between user connections, for which the MGW does not support transcoding, is enabled. This for example enables switching between user connections for voice and multimedia.

The following embodiments, which are not limiting but rather exemplary, are particularly advantageous:

1. In the H.248/Q.1950 protocols in the case of signaling for the modification of a termination one or a plurality of voice element(s) is/are also used, with which the MGC instructs the MGW only to verify whether it can connect the terminations to each other in their new coding, after receipt of instructions to modify a plurality of terminations connected within the MGW.
2. In a preferred embodiment of 1 the MGW does not forward user data from and to the relevant terminations, once it has received an instruction to modify for said termination. After the verification specified in 1, the MGW restores the connection between the relevant terminations.
3. In a preferred embodiment of 1 and 2 the MGW cannot isolate the relevant termination immediately after receipt of the instruction from the MGC to modify but must wait until switching of the coding is prompted by means of a subsequent separate signaling with the (MGW) switching node at the other end of the user connection section. This breaks the user connection for a quite short period.
4. In a preferred embodiment of 1 to 3 the MGW cannot restore the connections immediately after the verification specified in 1 but must wait until switching of the coding at said terminations has also been prompted by means of separate signaling with the (MGW) switching node at the other ends of the user connection sections to be reconnected.
5. In a preferred embodiment of 1 and 2 the MGW can reconnect the originally connected terminations in their old coding, if the MGW determines during the verification specified in 1 that it cannot connect the terminations together in their new coding. The MGW can also signal this error to the MGC.
6. In a preferred embodiment of 5 the MGW can transmit the corresponding error message to the MGC as a response to the

instruction to modify the last termination. The MGC is then able to utilize mechanisms already existing in BICC, Q.1902.4 and Q.1950 to reject the modification of the user connections.

7. In a preferred embodiment of 1 and 2 an extension of the existing instructions to modify a termination is used as the voice element.

8. In a preferred embodiment of 7 this extension should be contained in the first corresponding instruction for a termination. Only after the arrival of the last corresponding instruction for a connected termination should the MGW verify whether it can connect the terminations together in their new coding. This solution is easily inserted into the existing BICC message flows. No additional messages are required, just new voice elements within existing messages.

9. In a preferred embodiment of 8 the newly inserted voice element can be included in all instructions to modify originally connected terminations. This simplifies the task of the MGC and the MGW.

10. As an alternative to 8, in a preferred embodiment of 7 an extension can be included in the first instruction and also optionally in further instructions to modify connected terminations. This extension instructs the MGW not to implement a verification according to 1 until an instruction is received with an additional extension. This additional extension

instructs the MGW to implement the verification according to 1.

11. In a preferred embodiment of 7 the newly inserted voice element can be a characteristic of the so-called H.248 context.

12. As an alternative to 11 in a preferred embodiment of 7 the newly inserted voice element can be a characteristic of the so-called H.248 termination.

13. As an alternative to 7 in a preferred embodiment of 1 and 2 the MGC can isolate a termination by a specific instruction, before the MGC modifies the coding at said termination. Once the MGC has also modified the coding at one or a plurality of

other originally connected terminations, the MGC can reconnect the isolated termination by a further specific instruction.

14. In a preferred embodiment of 13 the MGC can isolate a termination by moving it into another so-called H.248 context.

5 15. In a preferred embodiment of 13 and 14 the MGC can use the so-called Q.1950 instructions "Isolate" and "Join".

#### BRIEF DESCRIPTION OF THE DRAWINGS

Further features and advantages of the invention will emerge  
10 from the Claims and subsequent description of an exemplary embodiment with reference to the drawing, in which:

Fig. 1 shows as an example the BICC message flow in the event of the inventive switching of a user connection from one  
15 coding to another coding.

#### DETAILED DESCRIPTION OF THE INVENTION

In Figure 1 the numerals indicate the time sequence of the messages they designate. Messages within the borders of the  
20 elements "Termination A" and "Termination B" relate respectively to messages from the MGC to the MGW, which relate to the corresponding termination, in particular the coding to be modified of the corresponding termination. The messages 2, 3, 4, 5, 7 and 9 are respectively confirmed by a message  
25 following immediately in the reverse direction (not shown for purposes of clarity).

The MGW is a media gateway, i.e. a switching device in a telecommunication network, and can be connected to one or a plurality of further MGWs in a packet and/or line switched  
30 manner for the transmission of user data (voice, text, multimedia) and/or signaling data (3, 7).

The MGC is a controller which controls the MGW (MGC = media gateway controller) and can be connected to one or a plurality

of further MGCs for sending and receiving signaling data (1, 6, 8, 10).

The terminations "Termination A" and "Termination B" (= user  
5 connection section terminations) are terminations of a section  
of a user connection switched through the MGW, e.g. for voice  
or multimedia (sound and image) at the MGW. The MGW sends  
and/or receives (user) data associated with the user connection  
through this termination to/from other MGWs. User data  
10 therefore arrives and/or user data is sent respectively via the  
terminations "Termination A" and "Termination B".

In the present instance the MGC receives the instruction 1  
(Modify codec) to modify the codec (e.g. voice codec) used for  
15 a user connection. The MGC knows that this user connection is  
switched by the MGW via the terminations "Termination A" and  
"Termination B" in Figure 1 and that it must therefore instruct  
the MGW to modify these terminations. The MGC then uses the  
messages 2 (Q.1950 "Reserve characteristics") and 5 (Q.1950  
20 "Modify characteristics") with new voice elements for this  
purpose.

On receipt of the instruction 1 the MGC sends the message 2  
"Reserve characteristics" to the MGW. This message 2 contains  
25 an instruction from the media gateway controller MGC to the  
media gateway MGW to modify the characteristics of a  
"Termination B" connected to the media gateway. On receipt of  
the message 2 the MGW sends a message 3 "Modify bearer", where  
necessary via the connection of the "Termination B" to another  
30 MGW, prompting this other MGW to modify locally the  
characteristics of the bearer of the user connection section to  
the "Termination B", e.g. the bandwidth. The MGW then confirms  
successful completion to the MGC by means of the "Bearer  
modified" message 4.



On receipt of the instruction 4 the MGC also sends the MGW the message 5 "Modify characteristics". This message 5 contains an instruction from the media gateway controller MGC to the media gateway MGW to modify characteristics (specifically the coding here) of a "Termination A" connected to the media gateway. The MGW also receives a message 7 "Modify bearer" here via the connection of the "Termination A" from another MGW, as this other MGW was informed of the planned modification of the coding for the connection of the "Termination B" via the signaling 6 to the MGC via an MGC/MGW (not shown).

In some instances the MGC receives a message 8 "Successful codec modification" from another MGC (not shown) relating to a successful codec modification in the other MGC.

The message 9 "Confirm characteristics" is used by the MGC to confirm to the MGW that it should retain the new characteristics (codecs).

The MGC uses the message 10 "Successful codec modification" in relation to a successful code modification in the MGW shown to confirm to another MGC (not shown) that a successful codec modification has taken place (in the MGW shown).

According to the invention the described message flow can be used and/or modified as follows. Three alternative methods a) to c) are described:

a) Method according to points 1 to 9 and 11 and 12 above: The MGC instructs the MGW in the message 2 by means of a new voice element only to implement a verification in respect of necessary transcoding after receipt of instructions for all connected terminations (here messages 2 and 5) and if necessary to insert a transcoder. On dispatch of the message 3 the MGW

isolates the termination B, so no user data can initially be transmitted via the termination B. On receipt of the message 5 the MGW determines that instructions have now been received for all terminations. The MGW then verifies whether connection of the terminations A and B is possible in the new coding. If this is not possible, the MGW sends a corresponding error message in the confirmation of receipt in relation to 5. Further error signaling is not shown here. Otherwise the MGW reconnects the terminations A and B using the new coding after receipt of the message 7.

b) Method according to points 1 to 7 and 10 to 12 above: The MGC instructs the MGW in the message 2 by means of a new voice element only to implement a verification in respect of necessary transcoding after receipt of a correspondingly marked instruction for a connected termination and if necessary to insert a transcoder. On dispatch of the message 3 the MGW isolates the termination B, so initially no user data can be transmitted via the termination B. In the message 5 the MGC instructs the MGW by means of a further new voice element to implement the specified verification. The MGW then verifies whether connection of the terminations A and B is possible in the new coding. If this is not possible, the MGW sends a corresponding error message in the confirmation of receipt in relation to 5. Further error signaling is not shown here. Otherwise the MGW reconnects the terminations A and B using the new coding after receipt of the message 7.

c) Method according to points 1 to 6 and 13 to 15 above: The MGC instructs the MGW immediately before dispatch of the message 2 by means of the additional message "Isolate" (not shown) to isolate the termination B. The MGE then forwards no user data to the termination B and also receives no user data from there. On receipt of the message 2, the MGW does not

verify whether transcoding is necessary to the termination A,  
as the two terminations are not connected. On receipt of the  
confirmation of the message 5 and before dispatch of the  
message 6, the MGC instructs the MGW by means of the additional  
5 message "Join" (not shown) to connect the termination B to the  
termination A. The MGW then verifies whether connection of  
terminations A and B is possible in the new coding. If this is  
not possible, the MGW sends a corresponding error message in  
the confirmation of receipt in relation to 5. Further error  
10 signaling is not shown here. Otherwise the MGW reconnects the  
terminations A and B using the new coding after receipt of the  
message 7. As an alternative to the above, the additional  
messages "Isolate" and "Join" can also relate to the  
termination A.

15